

User Manual

1. Layout



OBDII socket



LED Light

LED Flash: Connecting

LED Blue: Bluetooth connected

LED Off: Sleep Mode

iOBD2 mini

Note :

- a. iOBD2 mini dongle will enter sleep mode automatically when disconnected from your phone or tablet for 5 mins.
- b. Tips: unplug the iOBD2 mini when the vehicle is not to be used for longer periods.
- c. Driving data will still be recorded when iOBD2 and phone or tablet are not connected.
- d. For best performance use, iOBD2 mini with only one vehicle.
- e. Compatible with iPhone 4S and above; iPad 3 and above.
- f. Compatible with Android 4.3 and above.

2. Installation Instruction

2.1 Download the latest iOBD2 APP from Apple App Store or Google Play Store; or scan following QR Code to download it:



2.2 Plug iOBD2 mini into the vehicles OBDII socket

2.3 Run iOBD2 APP

2.4 Select the vehicle brand and model

2.5 Turn ignition on

2.6 Click setting menu, select hardware iOBD2 mini

2.7 Finish

3. Function

I Read fault code

I Clear fault code

I Live data

I Performance test

0~400 meter acceleration test

I Data logger

Record driving data (maximum 16000 trips)

I HUD

4. Packing list

iOBD2 mini X1 ;

User Manual X1 ;

5. Specification

Flash: 2MB

Working Voltage : 9 V~15 V

Electric Current : < 30 mA

Sleep-mode Electric Current : < 3 mA

Working Temperature : -25°C~75°C

Storage Temperature : -40°C~85°C

Working Humidity : < 60 %

Storage Humidity : < 80 %

Dimension : 48 * 42 * 25 (mm)

Net Weight : < 50 g